




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: B01D 69/02, B01L 3/00, B01D 71/02, 67/00, 69/10, 63/08, 61/14, 39/16	A1	(11) International Publication Number: WO 97/00121 (43) International Publication Date: 3 January 1997 (03.01.97)
(21) International Application Number: PCT/US96/09946 (22) International Filing Date: 14 June 1996 (14.06.96) (30) Priority Data: 60/000,281 16 June 1995 (16.06.95) US (71) Applicant: THE UNIVERSITY OF WASHINGTON [US/US]; 1107 N.E. 45th Street, Seattle, WA 98105 (US). (72) Inventors: BRODY, James, P.; 526 Yale Avenue North #310, Seattle, WA 98109 (US). OSBORN, Thor, D.; 31757 N.E. 102nd Place, Carnation, WA 98014 (US). (74) Agents: GREENLEE, Lorraine, L. et al.; Greenlee, Winner and Sullivan, P.C., Suite 201, 5370 Manhattan Circle, Boulder, CO 80303 (US).		(81) Designated States: European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: TANGENTIAL FLOW PLANAR MICROFABRICATED FLUID FILTER (57) Abstract <p>A microfilter utilizing the principles of tangential flow to prevent clogging, and sloped channel sides to overcome surface tension effects is provided which has feed inlet and exit connected by a feed flow channel; a barrier channel parallel to the feed flow channel, and a filtrate collection channel parallel to the barrier channel so that liquid can flow from the feed flow channel through the barrier channel which is too small to accommodate the particles, into the filtrate collection channel, and from then through a filtrate flow channel to a filtrate exit. Several picoliters of cell-free plasma are recovered from one drop of blood for analysis.</p> 		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

TANGENTIAL FLOW PLANAR MICROFABRICATED FLUID FILTER

This invention was made with government support under Army research contract DAMD17-94-J-4460 awarded by the U.S. Army. The government has certain rights in the invention.

5 Cross-reference to Related Applications

This is a utility patent application taking priority from provisional patent application 60/000281 filed June 16, 1995, which is incorporated herein by reference.

Field of the Invention

10 This invention relates generally to microfilters useful, for example, for separating plasma from whole blood. Analyzable quantities of plasma, i.e., from about 1 picoliter to a few hundred nanoliters, can be separated from one drop of whole blood within a few seconds by microfilters of this invention.

15 Background of the Invention

Many blood tests must be performed on plasma without cellular matter present. In the standard laboratory protocol, pure plasma is obtained through centrifugation. In order to produce a miniaturized blood sensor, a method to separate plasma
20 other than centrifugation is needed.

Chemical analysis of biological samples is constrained by sample size. Withdrawing a few milliliters of blood from an adult may have little effect, but repeating this procedure every hour or even withdrawing this amount once from an infant can
25 significantly alter the health of the subject. For these

reasons, a miniaturized blood analysis system would be useful. Furthermore, while many sophisticated tests that have great importance for critical care can be performed in major hospital laboratories, a substantial impact could be made on the practice of emergency medicine if some key tests could be performed on the patient at the site of injury.

Microfabricated fluid filters exist in the literature; however, these lack the advantages of the microfilter of the present invention.

Kittisland, G., and Stemme, G. (1990), "A Sub-micron Particle Filter in Silicon," Sensors and Actuators, A21-A23:904-907; and Stemme, G. and Kittisland, G. (1988), "New fluid filter structure in silicon fabricated using a self-aligning technique," Appl. Phys. Lett. 53:1566-1568, describe microfilters fabricated using a silicon wafer and capable of filtering out particles down to 50 nm. This filter design cannot be etched into the surface of a silicon wafer. Further, although these filters seem to perform well for gases, surface tension causes problems when filtering liquids. Gravesen, P., et al. (1993), "Microfluidics - a review," J. Micromech. Microeng. 3:168-182.

Wilding, P., et al. (1994), "Manipulation and Flow of Biological Fluids in Straight Channels Micromachined in Silicon," Clin. Chem. 40:43-47 disclose microfilters useful for separating blood cells from plasma etched into silicon wafers using a photolithographic process. These filter designs do not allow tangential or crossflow of the feed material past the barrier, which may be a narrower channel or barrier posts, to clear the barrier of particles. Further, in all cases, pressure must be applied to the system to obtain analyzable quantities of plasma. Because the minimum dimension of these filters is determined by a photolithographic process, they have a limit of about 1 micron. The photolithographic process is more sensitive to defects and requires tighter constraints on manufacturing than a process that relies on etching time to define the size of the channels as is

used herein.

Wilding, P., et al. U.S. Patent 5,304,487 issued April 19, 1994 discloses mesoscale analytical devices for fluid handling comprising flow channels and fluid handling regions micromachined into silicon wafers. Again, no microfilters having tangential flow capabilities to aid in keeping the barrier free of particles are disclosed.

Raehse, W., et al. U.S. Patent No. 4,751,003 issued June 14, 1988 discloses a microfilter using a crossflow principle having polysulfone tubes with micropore diameters of 0.3 to .5 microns disposed in a cylindrical configuration. Ehrfeld, W. et al. U.S. Patent No. 4,797,211 issued January 31, 1989 discloses a crossflow microfilter comprising a microporous membrane having slit-shaped cross-sections. Solomon, H., et al. U.S. Patent No. 4,212,742 issued July 15, 1980 discloses a filtration apparatus for separating blood cells from liquids utilizing crossflow principles comprising multiple layers and membrane filters.

Ehrsam, C. et al. U.S. Patent No. 4,801,379 issued January 10, 1989 discloses a microfilter made of a foil having pores set into protuberances on the foil to aid in prevention of clogging. Hillman, R. U.S. Patent 4,753,776 issued June 28, 1988 discloses a microfilter useful for separating plasma from red blood cells comprising glass fibers using capillary action to promote flow.

Shoji, S. and Esashi, M. (1994), "Microflow devices and systems," J. Micromechanics and Microengineering 4:157-171, provide a general review of microvalves, micropumps, microflow sensors and integrated flow systems.

None of the foregoing references disclose or suggest the microfilter design disclosed herein which provides for tangential flow, ease and control of manufacturing, and minimization of surface tension problems.

All patents and publications referenced herein are incorporated by reference herein in their entirety.

Summary of the Invention

5 This invention provides a microfilter useful for treating a feed liquid to separate liquid from particles contained therein comprising the following elements:

- a) a feed inlet;
- b) a feed exit;
- 10 c) a feed flow channel having a minimum dimension sufficient to permit flow of the particles and liquid therethrough, disposed between and in fluid communication with the feed inlet and the feed exit;
- d) a filtrate collection channel parallel to the feed flow channel;
- 15 e) a barrier channel parallel to, between, and in fluid communication with the feed flow channel and the filtrate collection channel; the barrier channel having a minimum dimension sufficiently small to permit flow of the liquid but not the particles
- 20 therethrough;
- f) a filtrate exit in fluid communication with the filtrate collection channel;

wherein the elements are formed into the surface of a horizontal substrate; and

25 wherein the surface of the horizontal substrate is covered by a lid.

Preferably the microfilter also comprises a filtrate outlet channel connecting the filtrate collection channel and the filtrate exit.

Methods for making and using the microfilters of this invention are also provided.

Brief Description of the Figures

Figure 1 is a schematic diagram of a filter design of this invention (not to scale).

Figure 2 is a cross section taken along line 2-2 of Figure 1 showing the feed flow channel, barrier channel and filtrate collection channel of a microfilter of this invention.

Detailed Description of the Preferred Embodiments

Figure 1 shows a microfilter of this invention comprising a feed inlet 1 depicted as a square port, a feed exit 2 depicted as a square port, a filtrate exit 3 depicted as a square port, a feed flow channel 4 connecting the feed inlet 1 and feed exit 2, a barrier channel 5 disposed between the feed flow channel 4 and filtrate collection channel 6, and a filtrate outlet channel 7 connecting the barrier channel 5 with the filtrate exit 3.

Feed liquid containing particles enters at feed inlet 1 at the upper right and flows to feed exit 2 at the upper left. Some particle-free fluid is pushed across barrier channel 5 into filtrate collection channel 6 and from thence down to filtrate exit 3 through filtrate outlet channel 7. By controlling the pressure drop between the feed inlet 1 and the filtrate exit 3, it is possible to control how quickly and how much filtrate is drawn out. Shear forces in the feed flow channel 4 act to prevent clogging of barrier channel 5 by particles.

Figure 2 is a cross section (not to scale) taken along line

2-2 of Figure 1 showing feed flow channel 4, barrier channel 5 and filtrate collection channel 6 as well as substrate 11 and lid 10. The channels in the silicon substrate are etched using an anisotropic etchant to give characteristic V-shaped grooves. The corners between feed flow channel 4 and feed inlet 1, between feed flow channel 4 and feed exit 2, and between filtrate collection channel 6 and filtrate exit 3 are not actually as sharp as shown, resulting in an enlargement of the cross-section of the channels as they interface with the inlet and exits, which is critical to preventing surface tension lock in the absence of pressurization of the system. The barrier channel is etched in a different step from the flow channels and can be anywhere from 0.010 micron to a few microns deep. The lid is preferably Pyrex glass attached to the substrate by anodic bonding, as is known in the art. In practice, the lid may have a tendency to bow in and may tend to close off channels such as barrier channel 5 which may be less than one micron deep. To solve this problem, spacers may be designed in the barrier channel by etching the channel to leave unetched bridges across it. Preferred spacers are about 10 microns long, placed at 30 micron intervals across the width of barrier channel 5.

The term "microfilter" means a filter capable of separating fluid from particles down to 0.1 microns or less in size (average diameter). Thus the barrier channel may have a depth less than 0.1 micron, i.e., at least sufficiently small that 0.1 micron particles are unable to flow therethrough. In another embodiment, the barrier channel has a depth of about 0.01 micron so that particles down to near 0.010 micron in size are unable to flow through. The flow channels preferably have depths from about 0.1 micron up to about 300 microns, and widths preferably from about 0.1 micron to about 500 microns, although they may be wider if desired. The microfilters of this invention are designed to handle small quantities, e.g. less than about 10 microliters, and preferably about 1 microliter (less than one drop) of feed liquid and are capable of providing filtrate in analyzable quantities, such as picoliter and nanoliter amounts,

e.g., between about one picoliter and about 500 nanoliters, when one microliter of feed liquid is used.

5 The feed liquid may be any liquid comprising particles too large to flow through the barrier channel. Preferably the feed liquid is blood, the liquid to be separated is plasma, and the particles are blood cells. Red blood cells are disk-shaped, about 2 microns thick and about 8 microns in diameter. White blood cells are irregularly shaped, averaging about 15 microns in diameter. Cell-free plasma is produced at the filtrate exit. 10 Preferably the liquid is a polar liquid, more preferably an aqueous liquid. The microfilter may be designed for use with polar or nonpolar liquids. The surfaces of the microfilter should be treated, as is known to the art, to render them hydrophilic or hydrophobic such that they will be wetted by the 15 type of feed liquid used.

The microfilters of this invention are capable of separating an analyzable quantity of liquid from a feed liquid containing particles which are too large to pass through the barrier channel. It is not necessary that the microfilters of this 20 invention be capable of removing all the particles present in all the feed liquid, only that a sufficient quantity of filtrate free of larger particles be delivered from the filtrate exit of the microfilter to permit analysis thereof. The desired output of the microfilters of this invention is a quantity of liquid from 25 which particles have been removed, rather than the particles themselves or the full amount of the feed liquid.

The feed inlet 1 may be any size and shape capable of receiving sufficient feed liquid to provide an analyzable quantity of filtrate liquid. The feed inlet may be a feed inlet port as shown in Figure 1, etched into the horizontal substrate as depicted in Figure 1; however, the feed inlet may be part of 30 another connected device used for previous handling of the feed liquid, e.g., heating, separation, mixing, etc. Preferably the feed inlet is a square-shaped hollow etched completely through

the silicon wafer of the preferred embodiment, about 1 mm by 1 mm, having approximately the same depth as the feed flow channel. Connections with other devices are then made from the rear of the wafer. Because of the etching process used in the preferred
5 embodiment in which the etchant attacks the {100} planes of the silicon substrate, the feed inlet 1 of the microfilter of Figure 1 will have sides sloping at an angle of about 55 degrees.

The feed exit 2 may similarly be of any size and shape convenient for collection of feed liquid from which some or none
10 of the particles and some of the liquid have been removed and may be part of a connected device used for further handling or disposal of the feed liquid. The feed exit 2 may be a feed exit port as shown in Figure 1 of the same size and shape as the feed inlet 1.

The feed flow channel 4 connecting the feed inlet 1 and the feed exit 2 should have a narrowest dimension wide enough to accommodate the particles in the feed liquid as it flows from the feed inlet 1 to the feed exit 2 past the barrier channel 5, and to provide a flow velocity under the influence of capillary
15 action sufficient to provide a Reynolds number less than that at which inertial effects are negligible, as is more fully discussed hereinafter. In a preferred embodiment hereof, the feed flow channel 4 has a width of about 50 to about 200 microns, a depth of about 50 to about 200 microns, and is substantially V-shaped.
20 However, the feed flow channel can be as wide and deep as desired.
25

A filtrate collection channel 6 runs generally parallel to the feed flow channel 4. The filtrate collection channel 6 preferably is as long as possible to maximize the throughput, and together with filtrate outlet channel 7 should have a volume
30 large enough to collect an analyzable quantity of filtrate. Preferably, the filtrate collection channel 6 is a few millimeters long, e.g., about 3-5 mm, and of the same depth, width and shape as the feed flow channel 4, although it may be

a wide pool or reservoir. It may be any shape capable of holding the collected filtrate.

The feed flow channel 4 and the filtrate collection channel 6 are separated from each other by a barrier channel 5 having a smaller minimum dimension than the feed flow channel 4 such that liquid may pass from the feed flow channel 4 and flow into the barrier channel 5 and from there into the filtrate collection channel 6, but the particles desired to be separated from the feed liquid remain in the feed flow channel 4. The barrier channel 5 is of a length sufficient to allow flow of sufficient liquid for analysis from the feed flow channel 4 even in the absence of system pressurization. Preferably, the barrier channel is the same length as the filtrate collection channel 6. In a preferred embodiment, the barrier channel 5 is about the same width as the feed flow channel 4, although it may be wider to provide greater ease of fabrication consistent with facilitating throughput. The barrier channel 5 may have a depth of less than about 0.1 micron down to about 0.010 micron, and preferably has a depth about 0.5 micron or less. This will preclude blood cells having a maximum dimension of about 8 microns or larger from passing through the barrier channel. The barrier channel 5 is generally too shallow to have the substantially V-shaped profile of the flow channels.

Where no external pressure is present, the surface tension of the fluid alone should be enough to provide initial wetting of the device. This initial wetting provides some flow across the barrier channel 5 and hence some particle-free fluid in filtrate collection channel 6. To prevent surface tension lock, it is important to provide for gradual changes in the curvature of the fluid/air interface. Where there is an abrupt change in the diameter of a channel (from narrow to wide), fluid will not flow through by means of capillary action alone; however, if the diameter change is gradual, capillary action will cause sufficient fluid flow through the filter to produce analyzable quantities of filtrate. The etching process of this invention

provides gradual widening of feed flow channel 4 as it connects with the feed inlet 1 so as to prevent surface tension lock, and provides gradual widening of filtrate outlet channel 7 as it connects with filtrate exit 3 to prevent surface tension lock.

5 The arrangement of the barrier channel 5 with respect to the feed flow channel 4 provides a tangential flow of the feed liquid past the barrier channel which tends to avoid clogging of the barrier channel, as the particles are swept into the flow of the feed material toward the feed exit.

10 The filtrate collection channel 6 is preferably the same length as the barrier channel 5 and is in fluid communication with it along its entire length to allow maximum flow of filtrate liquid toward the filtrate exit 3.

15 The filtrate exit 3 has a volume sufficient to accommodate an analyzable quantity of filtrate as discussed above. Again, the filtrate exit 3 can be part of a connected device such as a device for performing a separation, heating, mixing, or analytical step, for example as described in Wilding et al., U.S. Patent No. 5,304,487. Preferably, the filtrate exit 3 is a
20 filtrate exit port as shown in Figure 1 of the same size and shape as feed inlet 1.

25 The filtrate exit 3 is in fluid communication with the filtrate outlet channel 7 preferably by means allowing free flow of filtrate into the filtrate exit 3 in the absence of pressurization of the system. In other words, the surface tension of the filtrate flowing into the filtrate exit 3 must be capable of being overcome by the pressure exerted by capillary action alone. The filtrate may be removed from filtrate collection channel 6 by any means known to the art. The filtrate
30 collection channel 6 may comprise the filtrate exit point. Preferably, the filtrate exit 3 is connected to the filtrate collection channel 6 by a filtrate outlet channel 7 having a conformation which permits free flow of the filtrate therethrough

against the force exerted by surface tension, e.g., gradual changes in curvature rather than sharp edges. As more fully discussed hereinafter, the etching process used to form the substantially V-shaped channels of this invention results in a gradual widening of the channels sufficient to overcome the force of surface tension as discussed above.

The microfilter of this invention is capable of being formed on a substrate by microfabrication techniques known to the art, preferably by etching the flat surface of a silicon wafer and cutting to form a device about 1 cm by about 1 cm, and about 300 microns thick. Preferably these are {100} wafers (n-type or p-type) having at least about 100 to about 500 nm of silicon dioxide grown on the surface.

The length of the channels is between about 1 micron and several millimeters, and the depth anywhere from about 0.010 micron to the thickness of the wafer, e.g., about 300 microns. The width may be about 0.1 micron to about 500 microns.

The microfilter of this invention is completed by the addition of a lid placed over the surface of the substrate, touching the raised portions, and providing a top surface for enclosing the channels and ports. Preferably this lid is transparent, and more preferably is glass bonded to the surface of the substrate.

Means for applying pressure to the flow of the feed liquid through the device may also be provided. Such means may be provided at the feed inlet, the filtrate exit (as vacuum), or both. Means for applying such pressure are known to the art, for example as described in Shoji, S. and Esashi, M. (1994), "Microflow devices and systems," J. Micromechanics and Microengineering, 4:157-171, and include the use of a column of water or other means of applying water pressure, electroosmotic forces, optical forces, gravitational forces, and surface tension forces. Pressures from about 10^{-6} psi to

about 10 psi may be used, depending on the requirements of the system. Preferably about 10^{-3} psi is used when pressure is required.

When it is desired to reuse the microfilters of this invention, means for providing backflow of fluid across the barrier channel 5 to clear the particles therefrom may be provided. Pressurizing the filtrate exit 3 to about half the pressure being put on the feed inlet 1 generally provides sufficient backflow to clear the device.

In a preferred embodiment of this invention, microfilters of this invention have hydrophilic surfaces to facilitate flow of liquid therein and allow operation of the device without the necessity for pressurization. The substrate may be treated by means known to the art following fabrication of the channels, to render it hydrophilic. The lid is also preferably treated to render it hydrophilic.

The preferred process for making microfilters of this invention comprises:

a) providing a {100} silicon wafer;

b) etching a feed flow channel and a filtrate collection channel into the silicon wafer of step a) with an etchant capable of attacking the {100} planes of said silicon wafer to form substantially V-shaped channels; and

c) etching a barrier channel into said silicon wafer.

A {100} silicon wafer is one in which the major surfaces are substantially {100} planes, although sometimes the orientation in these commercially available wafers is not precise. The etching is preferably done using EPW F-etch as described in Reisman, A., et al. (1979), J. Electrochem. Soc. 126:1406-1415,

or another etchant capable of forming substantially V-shaped channels such as potassium hydroxide in a mixture of water and isopropyl alcohol. Preferably the etching is done in three stages, timed to provide the required depth for the channels and ports. In the embodiment of Figure 1, the inlet and exit ports are preferably etched in a first step, flow channels are preferably etched in a second step, and the barrier channel, which is the shallowest, is preferably etched in a third step. As is understood by those skilled in the art, the previously-etched structures are deepened during subsequent etching steps.

A lid, preferably a glass sheet, is then bonded to the etched substrate to complete the enclosure of the ports and channels. In a preferred embodiment, the substrate and lid are first treated to render them hydrophilic.

In use, a liquid, preferably about one microliter of blood, is injected into the feed inlet 1. The liquid moves through the filter by capillary action and several picoliters of filtrate collect at the filtrate exit 3 for analysis.

Means for injecting feed liquid into the device are provided, as when the microfilter of this invention is used as part of an analytical system. Such means include standard syringes and tubes. Means for removing fluid from the filtrate exit 3 may also be provided, including receptacles for the fluid, inducing flow by capillary action, pressure, gravity, and other means known to the art as described above. Such receptacles may be part of an analytical or other device for further processing the filtrate.

Analysis of the filtrate may be by optical means known to the art such as absorption spectroscopy or fluorescence, by chemical or immunological means, or other means known to the art to detect the presence of an analyte such as a virus, DNA sequence, antigen, microorganism or other factor.

The manufacturing process of this invention minimizes the number of mask steps and wafer/wafer or wafer/glass bonding steps. In manufacturing the microfilters of this invention, size scaling is also considered. Fluid dynamic behavior is directly related to the Reynolds number of the flow. In microdevices, if the velocity decreases as the channel length (where the device is assumed to work in a fixed time at all scales), then the Reynolds number varies in proportion to the square of the length. As devices are miniaturized, the Reynolds number is inevitably reduced.

The Reynolds number is the ratio of inertial forces to viscous forces. As the Reynolds number is reduced, flow patterns depend more on viscous effects and less on inertial effects. Below a certain Reynolds number, e.g. 0.1 (based on lumen size for a system of channels with bends and lumen size changes), inertial effects can essentially be ignored. The microfluidic devices of this invention do not require inertial effects to perform their tasks, and therefore have no inherent limit on their miniaturization due to Reynolds number effects. Applicants' filter designs, while significantly different from previous reported designs, operate in this range.

The devices of the preferred embodiment of this invention provide a few hundred picoliters of plasma within a few seconds. They also may be reused. Clogging is minimized and reversible. The sizes and velocities (100 μm wide and 100 $\mu\text{m/s}$) indicate a Reynolds number ($R_e = \rho l v / \eta$) of about 10^{-2} so that the fluid is in a regime where viscosity dominates over inertia.

The magnitude of the pressure drop needed to obtain an average velocity, v , of a fluid with absolute viscosity, η , and density, ρ , through a circular channel (length, l , diameter, d) can be calculated from Poiseuille's Law (Batchelor, G.K., An Introduction to Fluid Dynamics, Cambridge Univ. Press 1967),

$$\frac{P}{l} = \frac{32\eta v}{d^2}$$

Using $v = 100 \mu\text{m}/\text{sec}$ and $d = 100 \mu\text{m}$, we get a pressure drop equivalent to about 0.3 mm of H_2O per cm of channel length. Since Poiseuille's equation is only strictly valid for circular flow channels and the channels of this invention are substantially V-shaped grooves, it can be considered only as an approximate relation between the variables represented.

When a liquid is introduced into a device there is at first an effective pressure, $P_{\text{eff}} = P_o + P_{\text{st}}$, equal to the sum of the applied pressure, P_o , and a pressure due to the surface tension,

$$P_{\text{st}} = \frac{\gamma \cos \theta}{r} .$$

P_{st} is a function of the surface tension of the fluid, γ , the contact angle of the fluid with the surface, θ , and the radius of curvature of the fluid surface, r .

For hydrophilic surfaces, $\cos \theta$ is close to 1, and for small channels no applied pressure is needed to wet the device. This is referred to as "wetting by capillary action." However, once the device is completely wet, one has to worry about the surface tension at the exit area. In the device described in the example hereof, the radius of curvature of the fluid in the exit area was several millimeters, so that the pressure due to the surface tension was negligible.

With a channel width of $100 \mu\text{m}$, P_{st} is about 1 cm of H_2O , so surface tension on the exit channel is significant. However, using an etchant such as EPW F-Etch as described below, which attacks the {100} planes of silicon, means that the corners as etched are not as sharp as shown in Figure 2. This results in a gradual widening of the channel to about 1 mm which reduces the effect of the surface tension.

This effect also occurs in the barrier region. Using an etchant that gives a vertical (90°) profile, instead of the 55° characteristic of the {100} planes of silicon, would require a

pressure as large as one atmosphere to overcome the surface tension in a 0.1 μm gap.

Since this filter design is self-priming, it can be operated in two modes. In "one-shot mode," a drop (one μl) of blood contacts the entrance port. The blood is drawn down the channel and plasma is drawn through the filter without any applied pressure. This provides several nanoliters of plasma within a few seconds. Once fluid fills the device, flow stops. If no way is provided to flush this sample out of the device, it would have only one use.

The second mode, continuous flow mode, requires an applied pressure head. The relative pressure between the feed inlet, feed exit, and filtrate exit can be controlled to provide a continuous stream of filtrate or to induce some reverse flow through the filter which is useful for removing particles stuck on or near the barrier channel.

Example

A three mask level process was used to fabricate a microfilter of this invention on a silicon wafer. The first level defined connection ports, which were etched completely through the wafer to the rear side of the silicon. The second level defined the fluid transport channels, and the third level defined the maximum size of particles which could flow through the filter.

Four inch chrome masks were made to these specifications by Photo Sciences, Inc. (Torrance, CA) and 3" wafers ({100}, n-type) with 500 nm of SiO_2 grown on them were used.

Wafers were cleaned in a Piranha bath (H_2SO_4 and H_2O_2) (2:1) before processing. A primer (HMDS spun on at 3000 rpm) was used to enhance photoresist adhesion. About one μm of AZ-1370-SF (Hoechst) photoresist was deposited by spin coating (3000 rpm),

and this was followed by a soft bake (30 min at 90°C).

A contact aligner was used to align and expose wafers. Exposure time was varied to yield best results. No post-exposure bake was done. Wafers were developed in AZ-351 (diluted 4:1) (Hoechst) for one minute and rinsed in DI water. Blue tack tape (Semiconductor Equipment Corporation, Moorpark, CA) was applied to the backsides of the wafers to protect the oxide from the oxide etch.

The wafers were immersed in a buffered oxide etch (BOE, 10:1 HF (49%) and NH_4F (10%)) for eleven minutes to completely etch away the unprotected oxide. The blue tack tape was removed by hand, and the photoresist was removed in an acetone rinse.

Silicon etching was done in a mixture of ethylene-diamine, pyro-catechol, and water (EPW F-etch as described in Reisman, A., et al. (1979) J. Electrochem. Soc. 126:1406-1415) set up in a reflux boiling flask. This etch attacks the {100} planes of silicon at a rate of about 100 μm an hour. Fluid attachment ports were etched in the first step for about three hours. Photoresist was again applied, and the mask containing flow channels between fluid ports and the barrier region was exposed. The wafers were developed and etched in this second step for about one hour. Photoresist was applied once more and the mask containing the barrier region was exposed. The wafers were developed and etched in the final step for about one minute.

After final processing, the wafers were once again cleaned in a Piranha bath and rinsed in DI water. They were then diced into individual devices about 1 cm by 1 cm.

Anodic bonding according to Wallis, G. and Pomerantz, D.I (1969) J. Appl. Physics 40:3946-3949, was used to attach Pyrex glass to the silicon devices. One inch square pieces of Pyrex glass (100 μm thickness) from Esco Products Inc. (Oak Ridge, NJ) were used. First, the silicon and Pyrex glass were immersed in

a solution of H_2O_2 , NH_4OH , and H_2O (1:4:6) heated to 50°C . This process removes any organic matter on the surfaces and also makes the surfaces hydrophilic. After 20 minutes in this solution, the silicon and Pyrex were rinsed with DI water and dried. Anodic bonding was done at 400°C with 400 V applied between the glass and the silicon.

Testing was done by flowing dilute suspensions of fluorescent microspheres through the device. One drop of $16\text{ }\mu\text{m}$ diameter fluorescing microspheres (1% solids, from Duke Scientific, Palo Alto, CA) was added to 5 ml of DI water. A similar mixture of $2.6\text{ }\mu\text{m}$ diameter spheres was also prepared. The $16\text{ }\mu\text{m}$ spheres fluoresce in the green and the $2.6\text{ }\mu\text{m}$ diameter spheres fluoresce in the red, making them easily discernible by eye.

This mixture was introduced into the device, and observations were made using a Zeiss ICM-405 inverted microscope. Fluorescence of the spheres was observed using a silicon intensified target camera (SIT-66x, from Dage-MTI) and observations were recorded on video tape. Some images were also digitized using a frame grabber (Data Translation) and NIH Image software.

The pressures at the inlet port and at the exit port of the filtered liquid were controlled by filling a tube to the appropriate height with liquid. The pressures at the exit port of the unfiltered feed liquid was held constant to within a few mm of H_2O .

The experiment proceeded by first inserting a mixture of fluid and particles at the inlet port. Once this wet the entire device (one-shot mode), some particle build-up on the edge of the barrier channel was observed. Typically, some $16\text{ }\mu\text{m}$ spheres would build up along the barrier channel, but not to any significant depth.

The solution containing 2.6 μm spheres was then added to the inlet. These spheres freely flowed through the feed flow channel and some crossed the barrier channel.

5 The filter exit port was then pressurized to about half the pressure being put on the feed inlet. This resulted in a backflow across the barrier, quickly forcing the 16 μm spheres back into the flowstream where they were carried to the feed exit port.

10 The fluorescent spheres with a 16 micron diameter were immediately visible in the inlet port, as well as a few flowing along the feed flow channel and some pressed against the barrier channel. None passed through the barrier channel. After the introduction of 2.6 μm spheres, these smaller spheres were easily seen. Most flowed along the feed flow channel but some easily
15 passed by the barrier which trapped the 16 μm spheres.

The preferred embodiments described above are illustrative rather than limiting of the invention. As will be readily understood by those skilled in the art, various materials, processes and parameters can be varied to achieve the objectives
20 of this invention to provide a microfilter capable of providing analyzable quantities of particle-free liquid, and utilizing the principles of tangential flow past the barrier channel to reduce clogging, and sloped channel walls to overcome the effects of surface tension. The invention is limited only by the scope of
25 the claims appended hereto.

Claims

1. A microfilter useful for treating a feed liquid to separate liquid from particles contained therein comprising the following elements formed into the surface of a horizontal substrate:

a) a feed inlet;

b) a feed exit;

c) a feed flow channel having a minimum dimension sufficient to permit flow of the particles and liquid therethrough, disposed between and in fluid communication with the feed inlet and the feed exit;

d) a filtrate collection channel parallel to the feed flow channel;

e) a barrier channel parallel to, between, and in fluid communication with the feed flow channel and the filtrate collection channel; the barrier channel having a minimum dimension sufficiently small to permit flow of the liquid therethrough but not the particles;

f) a filtrate exit in fluid communication with the filtrate collection channel; and

g) a lid covering the surface of the horizontal substrate.

2. The microfilter of claim 1 also comprising a filtrate outlet channel connecting the filtrate collection channel and the filtrate exit.

3. The microfilter of claim 1 also comprising means for

applying pressure to the flow of the feed liquid through the microfilter.

4. The microfilter of claim 1 having hydrophilic surfaces whereby the liquid flows through the microfilter from the feed inlet to the filtrate exit without the application of pressure.
5. The microfilter of claim 1 adapted for the separation of plasma from whole blood.
6. The microfilter of claim 1 wherein the feed flow channel and the filtrate collection channel are substantially V-shaped.
7. The microfilter of claim 2 wherein the feed flow channel, the filtrate collection channel and the filtrate outlet channel are substantially V-shaped.
8. The microfilter of claim 1 wherein the feed flow channel and the filtrate collection channel are approximately 100 microns wide.
9. The microfilter of claim 2 wherein the barrier channel has a minimum dimension of less than about 0.1 micron.
10. The microfilter of claim 1 wherein the substrate is a silicon wafer.
11. The microfilter of claim 10 wherein the channels are etched by an anisotropic etchant to provide gradual widening at the inlet and exits whereby flow therethrough by means of capillary action alone is facilitated.
12. The microfilter of claim 1 wherein the lid comprises a glass sheet.

13. The microfilter of claim 1 adapted to separate an analyzable quantity of plasma from one microliter of blood.

14. An analytical system comprising the microfilter of claim 1 and also comprising injection means for introducing the feed liquid into the feed inlet.

15. The microfilter of claim 1 comprising means in fluid communication with the filtrate exit for detecting the presence of an analyte in the filtrate.

16. A method for making a microfilter of claim 1 comprising:

a) providing a {100} silicon wafer;

b) etching a feed flow channel and a filtrate collection channel into the silicon wafer of step a) with an etchant capable of attacking the {100} planes of said silicon wafer to form substantially V-shaped channels; and

c) etching a barrier channel.

17. The method of claim 16 wherein steps a), b) and c) are performed sequentially using the same etchant.

18. The method of claim 16 wherein following the etching steps, a glass lid is bonded to the etched surface of the silicon wafer.

19. The method of claim 16 wherein the etchant used is an anisotropic etchant providing a gradual widening of the channels at the inlet and exits such that flow therethrough by means of capillary action alone is facilitated.

20. A method for recovering a quantity of liquid separated from particles from a feed liquid containing said particles

comprising introducing the feed liquid into the feed inlet of the microfilter of claim 1 and withdrawing separated liquid from the filtrate exit.

21. The method of claim 20 wherein the feed liquid is blood, the particles are blood cells, and the separated liquid is plasma.

22. The method of claim 21 wherein pressure is applied to the microfilter following withdrawal of separated liquid from the filtrate exit to clear the barrier channel of particles.




FIGURE 1




FIGURE 2

INTERNATIONAL SEARCH REPORT

Int. Application No

PCT/US 96/09946

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 B01D69/02 B01L3/00 B01D71/02 B01D67/00 B01D69/10
B01D63/08 B01D61/14 B01D39/16

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B01D B01L C12M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO,A,95 13860 (C.J.M. VAN RIJN) 26 May 1995 see the whole document	1-22
Y	--- PATENT ABSTRACTS OF JAPAN vol. 16, no. 169 (M-1239), 23 April 1992 & JP,A,04 014457 (OKI ELECTRIC IND CO LTD), 20 January 1992, see abstract	1-22
A	--- WO,A,79 01120 (THE GOVERNMENT OF THE UNITED STATES OF AMERICA) 27 December 1979 see claim 1 & US,A,4 212 742 cited in the application --- -/--	1

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

28 October 1996

Date of mailing of the international search report

21. 11. 96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Cordero Alvarez, M

INTERNATIONAL SEARCH REPORT

International Application No PCT/US 96/09946

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO,A,93 22053 (TRUSTEES OF THE UNIVERSITY OF PENNSYLVANIA) 11 November 1993 see claims 1,27; examples 1-3 & US,A,5 304 487 cited in the application -----	1,10,16

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 96/09946

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-9513860	26-05-95	NL-A- 9301971	01-06-95
		NL-A- 9401260	01-06-95
		AU-A- 1414095	06-06-95
		EP-A- 0728034	28-08-96

WO-A-7901120	27-12-79	US-A- 4212742	15-07-80
		CA-A- 1117029	26-01-82
		EP-A- 0016781	15-10-80

WO-A-9322053	11-11-93	US-A- 5304487	19-04-94
		US-A- 5296375	22-03-94
		AT-T- 140025	15-07-96
		AT-T- 140880	15-08-96
		AU-A- 4222393	29-11-93
		AU-A- 4222593	29-11-93
		AU-A- 4222693	29-11-93
		AU-A- 4222793	29-11-93
		AU-A- 4223593	29-11-93
		CA-A- 2134474	11-11-93
		CA-A- 2134475	11-11-93
		CA-A- 2134476	11-11-93
		CA-A- 2134478	11-11-93
		DE-D- 69303483	08-08-96
		DE-D- 69303898	05-09-96
		EP-A- 0637996	15-02-95
		EP-A- 0637997	15-02-95
		EP-A- 0639223	22-02-95
		EP-A- 0637998	15-02-95
		EP-A- 0637999	15-02-95
		JP-T- 7506430	13-07-95
		JP-T- 7506431	13-07-95
		JP-T- 7506256	13-07-95
		JP-T- 7506257	13-07-95
		JP-T- 7506258	13-07-95
		WO-A- 9322054	11-11-93
		WO-A- 9322421	11-11-93
		WO-A- 9322055	11-11-93
		WO-A- 9322058	11-11-93
		US-A- 5427946	27-06-95
		US-A- 5498392	12-03-96

INTERNATIONAL SEARCH REPORT

Information on patent family members

Internal Application No

PCT/US 96/09946

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-9322053		US-A- 5486335	23-01-96
